# **POWER UNITS**

# **6UZ1**

**SPECIFICATION** 



Isuzu Power Solutions. For those who never stop.











# AT A GLANCE

Power Output ■ Max. 270.0 kW / 362.1 hp

(rated) @ 1950 RPM ■ Max. 229.5 kW / 307.8 hp (cont.) @ 1950 RPM

Torque Output ■ Max. 1435 Nm @ 1500 RPM

**Displacement** ■ 9.8 L

Bore x Stroke ■ 120 x 145 mm

O/A Dimensions ■ 1368 mm (L) (engine only) ■ 1012 mm (W)

■ 1230 mm (H)

Dry Weight (engine only)

■840 kg

**Features** 

■ Turbocharged intercooled diesel engine

■ Common rail direct injection fuel system

■ Low noise, low fuel consumption, low maintenance

■ Easy to start

■ Reliable power

■ Water cooled

■ Tier-3 emission spec. reference

■ Genuine Isuzu engine manufactured in Japan

### ENGINE PERFORMANCE 1500 **Engine Power** 1000 1100 1200 1300 1400 1600 1700 1800 1900 1950 Rated (kW / hp) $114.0/152.9 \quad 134.0/179.7 \quad 158.0/211.9 \quad 180.0/241.4 \quad 200.0/268.2 \quad 225.4/302.3 \quad 240.0/321.8 \quad 250.0/335.3 \quad 260.0/348.7 \quad 268.0/359.4 \quad 270.0/362.1 \quad$ Continuous (kW / hp) 96.9/129.9 113.9/152.7 134.3/180.1 153.0/205.2 170.0/228.0 191.6/256.9 204.0/273.6 212.5/285.0 221.0/296.4 227.8/305.5 229.5/307.8



# **SPECIFICATIONS**

Туре:	Vertical water-cooled 4-cycle Diesel		
Model (Manufacturer):	6UZ1-XYBW01 (Isuzu)		
Emission Spec. Reference:	Tier-3 / Stage-IIIA		
Max. Rated Output:	270.0 kW (362.1 hp) @ 1950 RPM		
Continuous Output:	229.5 kW (307.8 hp) @ 1950 RPM		
Max. Torque	1435 Nm @ 1500 RPM		
Displacement:	9.8 L		
Combustion System:	Direct Injection (Turbocharged, Intercooled)		
O/A Dimensions:	1368 (L) x 1012 (W) x 1230 mm (H)		
Dry Weight:	840 kg		
Fuel Consumption:	69.0* L/h @ 100% load		

\*Based on diesel fuel with a specific gravity of 0.835 kg/m3 at 15°C. Actual value may vary.

## **POWER UNIT CONFIGURATIONS**

### 1. Starter (STR)

- Light duty air cleaner system
- Industrial grade exhaust system
- Engine mounting feet
- Heavy duty full aluminium cooling system (max. 45°C)
- 24V complete electrical system (incl. engine harness and stop solenoid)

# 2. Premium (PRM) Features include STR plus:

- Heavy duty air cleaner system (dual element)
- Air cleaner restriction indicator
- Residential grade exhaust system
- Skid rail chassis mounting
- High performance heavy duty cooling system (50°C +)
- IP65 'PR0' engine controller (advanced watchdog protection + application I/O)
- Remote oil drain kit

# KEY BENEFITS

### DESIGN

Australian designed and sourced engine mounts and skid

Australian designed heavy duty bar and plate all aluminium radiator

Premium quality air cleaners

Complete electrical engine harness (includes engine stop solenoid,

glow plug assisted start)

IP65 stainless steel ECM enclosure with LED indicators

## CONTROL PANEL

ComAp 'PRO' professional engine controller (advanced engine monitoring protection, plus customer application inputs/outputs, complete event history log, large easy to read display)



ComAp 'PRO' Controller

# OPTIONS

Premium pump pressure transducer range

4G remote monitoring and control kit

Low coolant alarm protection kit 160W solar battery charging kit

Extension harnesses

Coolant surge tank kit







Clutch option