POWER UNITS

3CB1

SPECIFICATION



Isuzu Power Solutions. For those who never stop.



Image included for illustrative purposes only.









AT A GLANCE

Power Output Max. 18.7 kW / 25.1 hp (rated)

@ 3200 RPM

Max. 15.9 kW / 21.3 hp (cont.)

@ 3200 RPM

Torque Output ■ Max. 63.5 Nm @ 2300 RPM

Displacement ■ 1.116 L

Bore x Stroke ■ 76 x 82 mm

O/A Dimensions ■ 570 mm (L) (engine only) ■ 455 mm (W)

■ 586 mm (H)

Dry Weight (engine only)

■117 kg

Features

■ Naturally aspirated diesel engine

■ Mechanical in-direct injection fuel system

■ Low noise, low fuel consumption, low maintenance

■ Compact and easy to start

■ Reliable power

■ Water cooled

■ Interim Tier-4 emission spec. reference

■ Genuine Isuzu engine manufactured in Japan

PERFORMANCE ENGINE **Engine Power** 1600 2600 3200 1400 1800 2000 2200 2400 2800 3000 Rated (kW / hp) 8.3 / 11.1 10.0 / 13.4 13.3 / 17.8 18.7 / 25.1 11.9 / 16.0 14.6 / 19.6 15.8 / 21.2 17.0 / 22.8 17.9 / 24.0 18.4 / 24.7 Continuous (kW / hp) 7.1 / 9.5 8.5 / 11.4 10.1 / 13.6 11.3 / 15.2 12.4 / 16.6 13.4 / 18.0 14.5 / 19.4 15.2 / 20.4 15.6 / 21.0 15.9 / 21.3



SPECIFICATIONS

Туре:	Vertical water-cooled 4-cycle Diesel	
Model (Manufacturer):	3CB1-CZP01 (Isuzu)	
Emission Spec. Reference:	Interim Tier-4 / Stage-IIIA	
Max. Rated Output:	18.7 kW (25.1 hp) @ 3200 RPM	
Continuous Output:	15.9 kW (21.3 hp) @ 3200 RPM	
Max. Torque	63.5 Nm @ 2300 RPM	
Displacement:	1.116 L	
Combustion System:	In-direct Injection (Naturally Aspirated)	
O/A Dimensions:	570 (L) x 455 (W) x 586 mm (H)	
Dry Weight:	117 kg	
Fuel Consumption:	6.5* L/h @ 100% load	

*Based on diesel fuel with a specific gravity of 0.835 kg/m3 at 15°C. Actual value may vary.

POWER UNIT CONFIGURATIONS

1. Starter (STR)

- Light duty air cleaner system
- Industrial grade exhaust system
- Engine mounting feet
- Heavy duty full aluminium cooling system (max. 45°C)
- 12V complete electrical system (incl. engine harness and stop solenoid)

2. Economy (ECY) Features include STR plus:

- Medium duty air cleaner system
- Skid rail chassis mounting
- · Mechanical vernier throttle kit
- IP65 'ECO' engine controller (essential watchdog protection)
- Engine RPM sender (MPU)

3. Premium (PRM) Features include ECY plus:

- Air cleaner restriction indicator
- Air cleaner rain/inlet hood
- Residential grade exhaust system
- High performance heavy duty cooling system (50°C +)
- Engine oil pressure and temperature senders
- IP65 'PR0' engine controller (advanced watchdog protection + application I/O)
- Remote oil drain kit

KEY BENEFITS

DESIGN

Australian designed and sourced engine mounts and skid

Australian designed heavy duty bar and plate all aluminium radiator

Premium quality air cleaners

Complete electrical engine harness (includes engine stop solenoid, glow plug assisted start and fuel pump)

CONTROL PANEL

DeepSea 'ECO' economy engine controller (provides essential engine monitoring protection)

ComAp 'PRO' professional engine controller (advanced engine monitoring protection, plus customer application

inputs/outputs, complete event history log, large easy to read display)





DeepSea 'ECO' Controller

ComAp 'PRO' Controller

OPTIONS

Heat Exchanged cooling package

Premium pump pressure transducer range

Longer application skid for mounting of auxiliary items

Flywheel stub shafts

Auxiliary PTO crankshaft pulley

4G remote monitoring and control kit

Low coolant alarm protection kit 160W solar battery charging kit

Extension harnesses

Coolant surge tank kit

24V electrical system

Energise to stop kit

Vibration isolation mounts



Transducer option



Heat Exchanger option



Clutch option

^{*}Note, some options may not be available on all engine models. Some options are already standard fitment on some engine models. Our goods and services come with guarantees that cannot be excluded under the Australian Consumer Law. For major failures with the service, you are entitled: To cancel your service contract with us; and to a refund for the unused portion, or to compensation for its reduced value. You are also entitled to choose a refund or replacement for major failures with goods. If a failure with the goods or a service does not amount to a major failure, you are entitled to have the failure rectified in a reasonable time. If this is not done you are entitled to choose a refund of replacement for major failures with goods. If a failure with the goods or a service does not amount to a major failure, you are entitled to have the failure rectified in a reasonable time. If this is not done you are entitled to refund for the goods and to cancel the contract for the service and obtain a refund of any unused portion. You are also entitled to be compensated for any other reasonable yor foreseeable loops from a failure in the goods or service. This warranty is given by Isuzu Australia Limited, ABN 97 005 962 572 (TAL') whose business address is 66 Foundation Road, Truganina, VIC 3029. IAL's telephone number is 1800 035 640. For further information on Isuzu warranties please visit www.powersolutions.isuzu.com.au. The information in this leaflet was correct at time of printing, but all measurements, specifications and equipment are subject to change without notice. Some equipment may have been changed and/or is available at extra cost. IAL may make changes at any time without notice, in prices, colours, materials, equipment and models. IAL makes all reasonable attempts to ensure the availability of all engines and equipment. The information in this leaflet is general in nature. Your Isuzu dealer can confirm all measurements, specifications and engine/equipment availability upon request. ARK011 06/21